

New Generation 668-2-4

Shown with Optional Bottom Blast Fan



Technical Specifications

● Extreme Height	107"/272 cm
Height with Bottom Fan Shown	124"/315 cm
● Extreme Width	86"/219 cm
● Extreme Length	180"/460 cm
● Width on Floor	71.5"/182 cm
● Length on Floor	174"/444 cm

Electrical Requirements

● Main Fan Motor	10 H.P./7.5 Kw
● Eccentric Motor	3 H.P./2.25 Kw
● Vibratory Feeder Motor	½ H.P./0.375 Kw

Air Output

6,400 CFM

Capacities*

● Small Seed	200-375 BPH (5.4-10.2 MT/Hr)
● Medium Seed	400-650 BPH (5.0-8.8 MT/Hr)
● Large Seed & Wheat	600-900 BPH (16.32-24.48 MT/Hr)
● Market/Pre Cleaning	1200-1800 BPH (32.65-49 MT/Hr)

Features

- Heavy duty construction – built to last
- Uses standard Clipper screens
- Variable Pitch Screens Available in Top Shoe
- Air Lock Trash Discharge Augers
- Six Screen Decks - 2 in Top Shoe & 4 in Bottom Shoe, 18 Screen sections – 54" x 26"

Options

- Bottom Blast Fan (Shown Above)
- Electronic Control Package (Shown Above)
- Grease Line Package

Note: *Capacities may vary depending on seed condition, moisture content, seed varieties, types and volumes of contaminants to be separated and the percentage of foreign material acceptable in the final product.



Sold and Serviced by



1440 SOUTH ADAMS STREET, BLUFFTON IN 46714 (260) 824-3400, (800) 248-8318, FAX (260) 824-5463
info@atferrell.com www.clipperseparation.com